$\begin{center} GRM153R60J475ME15\# \\ \begin{center} "#" indicates a package specification code. \end{center}$
















< List of part numbers with package codes > GRM153R60J475ME15D , GRM153R60J475ME15J

Shape



L size	1.0 ±0.2mm
W size	0.5 ±0.2mm
T size	0.3 ±0.03mm
External terminal width e	0.15 to 0.35mm
Distance between external terminals g	0.3mm min.
Size code in inch(mm)	0402 (1005M)

Notes

Derating1. Only for mobile devices



Packaging	Specifications	Minimum quantity
D	ф180mm Paper taping	10000
J	ф330mm Paper taping	50000

Mass (typ.)	
1 piece	1.3mg
φ180mm Reel	91g

Specifications

Capacitance	4.7μF ±20%
Rated voltage	6.3Vdc
Temperature characteristics (complied standard)	X5R(EIA)
Capacitance change rate	±15.0%
Temperature range of temperature characteristics	-55 to 85°C
Operating temperature range	-55 to 85°C

1 of 1



^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



^{2.} This datasheet has only typical specifications because there is no space for detailed specifications.